



Section 1: Identification of Chemical, Product and Company

Address: Unit 5/92 Township Drive, Burleigh Heads, Queensland, 4220
Telephone: 07 5576 6388
Web/E-mail: www.eximport.com.au or info@eximport.com.au
Trade name: Elleebana Lift Lockers
Product Use: Apparatus for styling of eyelashes
Creation Date: November 2023
Revision Date: November 2027

Section 2: Composition, Information on Ingredients

Pure Substance:

Ingredients I.N.C.I

INCI	CAS NO.	Wt(%)
Methyl vinyl polysiloxane	68083-19-2	56%~80%
Silicone dioxide	112945-52-5	18%~40%
Silicone oil	63148-62-9	2%~4%

Section 3: Hazards Identification

Health Harm : No Heavy metal, halogen, PAHS, 16P
Environmental : Not applicable
Major : Not applicable
Blast Hazard : Not applicable

Other Hazards

No data available

Section 4: First Aid Procedures

Skin contact: Wash thoroughly with soap and water, flush with plenty of water. Take off soiled clothes. Contact physician if symptoms persist

Eye contact: Rinse immediately with plenty of water for 10 minutes at least. Contact a physician if symptoms persist

Inhalation: Move to fresh air, sent to hospital for treatment

Ingestion: Wash the mouth with water, seek medical advice immediately

Section 5: Fire Fighting Measures

Hazard specialty: high temperature can result in easy burn

Extinguishing agent: Carbon monoxide, carbon dioxide, dry chemical, foam or water fog

Extinguishing Notes: N/A

Section 6: Accidental Release Measures

Personal Attention: N/A

Environmental Attention: N/A

Methods for cleaning up: Sweep, cleaning

Section 7: Handling & Storage

Operation Notes: No special notes

Storage note: Stored in a cool and ventilated warehouse and avoid the sun, cut off from sources of heat and fire.

Storage temperature 23-27 degrees Celsius

Section 8: Exposure Controls and Personal Protection

Project Control: No special notes

Respiratory system protection: No special notes

Eye Protection: No special notes

Body Protection: No special notes

Hand Protection: wash hands

First responders' protection: no special notes

Other protection: No special notes

Section 9: Physical and Chemical Properties

Appearance:	Rubber Crepe
Odour:	None
Colour:	Pantone 021C (Orange), Black and Transparent
pH:	Not applicable
Ignite temperature	Not applicable
Solubility:	Soluble in benzene
Major use:	Applicable to the production of ordinary silicon rubber products and miscellaneous pieces of ordinary silicon rubber keys-based adhesive, especially suitable for colour products, applicable to molding process

Section 10: Stability and Reactivity

Stability:	Stable.
Ban-compound substance:	oxidizer.
Conditions to avoid:	Not applicable
Hazardous decomposition products:	Combustion products: Silica, carbon dioxide and trace amounts of incomplete combustion of carbon.

Section 11: Toxicological Information

Acute toxicity:	N.A
Excitve:	N.A
Allergenicity:	N.A
Mutagenicity:	N.A
Carcinogenicity:	N.A
Subacute and Chronic Toxicity:	N.A

Section 12: Ecological Information

Ecological Toxicity:	N.A
Biology Degradability:	N.A
Abiological Degradability:	N.A
Biology Enrichment or biology accumulate property:	N.A
Other Effects:	Combustion products: Silica, carbon dioxide and trace amounts of incomplete combustion of carbon

Section 13: Disposal Considerations

Castoff Kind:	Normal Industry Castoff
Castoff treatment method:	Disposed compliance with the respective countries' national regulations

Section 14: Transport Information

Packing method:	Carton
Transport Notes:	No Special note

Section 15: Regulatory Information

Regulatory information N.A

Section 16: Other Information

This MSDS contains only safety-related information. For other data see product literature.